



Adjustable flow, Intelligent pump machine, Support to change the direction of liquid

KCP PRO adjustable speed peristaltic pump is a type of intelligent pump machine, user can switch and speed control on the pump via potentiometers, through the toggle switch to stop and reverse control.

Flow rate range: 24~190ml/min Motor lifetime: around 1000h

Operating conditions:

Temperature environment: 0~40°C

Relative humidity: < 80°C

Tubing selection: France, Saint-Gobain Norprene®

Weight: 765g (without power supply) 825g (with power supply)







Environmental protection



Instruments and equipment



Smart Home

Tube model	N19	N16	N40
Tube size	2.4*5.6mm	3.2*6.4mm	3.2*6.4mm
Flow rate (ml/min)	24~92ml/min	39~154ml/min	47~190ml/min
Tube material	France, Saint-Gobain Norprene® (Meet FDA Certification, Food process tube for critical processing applications in the food, dairy and cosmetic industries. Compatible with virtually all commercial cleaners and sanitizers. Great resistant to general chemicals, acid, alkali and oxidizing agents, working temperature 59°C-135°C)		
Positive Pressure	0.15Mpa		
Negative Pressure	-0.09Mpa		
Voltage	24V		
Current	0.3~0.35(A)		
Size	L139mm*W79mm*110mm		